

## LEDline 2.0 - 30mm wide

- Fully encapsulated linear lighting fixture made of anodised aluminium.
- Standard lengths: 25, 50, 75 & 100cm
- Height: 30 or 40mm
- Special lengths: on request
- IP68
- 4x IK10: 80 Joule
- IP68 connection system
- Operating temperature: -25°C to 60°C
- Colours: Cold white 6100K  
Neutral white 4100K  
Warm white 2800K  
Yellow  
Red  
Green  
Blue  
RGB
- Binning for white colours: 3 MacAdam
- CRI for white colours: 85
- Tension: 24Vdc
- Power ECO version: 3.5W/m  
PLUS version: 7W/m  
POWER version: 15W/m
- Power RGB ECO version: 9W/m  
PLUS version: 18W/m
- Dimmable

White monocolour		LEDline h: 40mm		LEDline h: 30mm	
		Lumen/m	Lumen/W	Lumen/m	Lumen/W
ECO (3,5W/m)	Diffuse	76	22	137	39
	Clear	156	45	163	47
PLUS (7W/m)	Diffuse	173	25	287	41
	Clear	339	48	338	48
POWER (15W/m)	Diffuse	438	29	692	46
	Clear	801	53	822	55

*The given data are typical values. Due to tolerances of the production process an the electrical components, light output values may vary.*

